10

15

20

WHAT IS CLAIMED IS:

- A process for producing a methyl methacrylate, the process comprising the steps of:
- decomposing methyl t-butyl ether to obtain an 5 isobutylene and a methanol,
 - (ii) oxidizing the isobutylene to obtain at least one compound selected from a methacrylic acid and a methacrolein and
 - (iii) esterifying at least one compound selected from the methacrylic acid and the methacrolein with the methanol to produce a methyl methacrylate.
 - 2. The process according to claim 1, further comprising a step of separating the isobutylene from the decomposition reaction mixture prior to the oxidation step of the isobutylene.
 - 3. The process according to claim 2, further comprising a step of recovering a methanol from the remaining mixture obtained after the separation of the isobutylene, prior to the esterification step.
- 4. The process according to claim 3, wherein the recovered methanol has a 95 % by weight or more of methanol based on the recovered methanol and contains at least one compound selected from t-butyl alcohol, water and methyl t-butyl ether.
 - The process according to claim 3, further comprising a step of purifying the recovered methanol.
- 25 6. The process according to claim 5, wherein the

purified methanol contains about 95 % by weight or more of methanol based on the purified methanol.

- 7. The process according to claim 5, wherein the purified methanol contains about 99% by weight or more of methanol based on the purified methanol.
 - 8. The process according to claim 5, wherein the purified methanol contains about 99.9 % by weight or more of methanol based on the purified methanol.
- An apparatus for producing a methyl methacrylate,
 the apparatus comprising:
 - (a) a reactor for catalytic decomposition of methyl t-butyl ether to obtain a reaction mixture containing an isobutylene and a methanol,
- (b) separation means for separating the isobutylene from 15 the reaction mixture,
 - (c) recovery means for recovering the methanol from the remaining mixture obtained after the separation of the isobutylene,
- (d) a reactor for oxidation of the isobutylene to obtain 20 at least one compound selected from a methacrylic acid and a methacrolein and
 - (e) a reactor for esterification of at least one compound selected from the methacrylic acid and the methacrolein with the methanol.
- 25 10. The apparatus according to claim 9, wherein the

methanol obtained by recovery means (c) has a concentration of about 95 % by weight.